

NOTES

- 1. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE SPECIFIED.
- 2. THIS STANDARD TO BE READ IN CONJUNCTION WITH APPLICABLE SPECIFICATIONS AND GSSD-1227.010.
- 3. MINIMUM HORIZONTAL DISTANCE BETWEEN SANITARY SERVICE AND FIRST UTILITY MUST BE 600 mm.
- 4. WATER SERVICE MUST BE INSTALLED ON THE OPPOSITE SIDE OF THE SANITARY SERVICE IN COMPARISON TO THE UTILITIES IN A SINGLE UTILITY TRENCH.
- 5. WHERE SERVICE CONNECTIONS ARE INSTALLED IN ROCK, THE ROCK SHALL BE BLASTED AND REMOVED TO 1.5 m BEYOND THE STREET LINE.



HORIZONTAL CONTROL OF LATERAL SEWER & WATER CONNECTIONS IN A COMMON ROCK TRENCH WITH OTHER UTILITIES

DRAWN BY: STS/RFRANK	REV No:
DATE: 2003-03-03	REV DATE:
SCALE: NTS	CAD/FILE No.:
APP'D:	A1977-1 (1 OF 1) GSSD-1226.010

DISCLAIMER OF WARRANTY: The data is provided "as—is", without warranty of any kind either expressed or implied. Any and all liabilities for damage, direct or indirect, however caused, and resulting in any way by use of the supplied data is the full and final responsibility of the user.

COPYRIGHT: All rights are reserved. No part of the supplied data may be reproduced, or transmitted to others, in any form or by any means, without the prior written permission of the CITY OF GREATER SUDBURY.