



2-10Mx1200 LONG-CORNER BARS -6-10M BARS GRATE ELEVATION CEMENT MORTAR STEEL TO BE ADJUSTMENT SUPPORTED UNITS: MIN OF ONE ROW TO MAX 300mm ON WIRE CHAIRS 4-10M BARS 650 SQ STEPS SET @ @ 50 c/c WALL THICKNESS 300 c/c SEE SEE NOTE 1 10M BARS @ NOTE 6 150 c/c EACH WAY 10M @ 300 EACH WAY FOUR SIDES -4-10M BARS @ 50 c/c 6-10M BARS & BOTTOM PLAN VIEW SLAB REINFORCING SCHEDULE SECTION D - D



CAST-IN-PLACE MAINTENANCE HOLE OR MAINTENANCE HOLE CATCHBASIN

MAX PIPE SIZE 825 mm 1275 mm x 1275 mm DEPTH 9.0 m MAXIMUM

DRAWN BY: S	TS/RF/SGI	REV No: 3
DATE: 2003-0)3-03	REV DATE: JAN/2013
SCALE: NTS		CAD/FILE No.:
SOALL. NTS		A1934-1 (1 OF 1)
APP'D:		GSSD-700.030

DISCLAIMER OF WARRANTY: The data is provided "as—is", without warranty of any kind either expressed or implied. Any and all liabilities for damage, direct or indirect, however caused, and resulting in any way by use of the supplied data is the full and final responsibility of the user. COPYRIGHT: All rights are reserved. No part of the supplied data may be reproduced, or transmitted to others, in any form or by any means, without the prior written permission of the CITY OF GREATER SUDBURY.